EMTECH® BS4568 / IEC61386 CONDUIT PIPE



Resort World Sentosa



REC @ Tuas



Alcon Factory @ Tuas



Temasek Laboratories and NUS Engineering Faculty



SMRT Projects



Orchard Residences



ITE West



BS4568 / IEC61386 Conduit Fittings & Accessories



Lonza Biomedical Plant at Tuas



Regency Suite



Marina Barrage



IM Flash

Copyright © 2008-2017 Tan Teck Seng Electric Co. Pte. Ltd. All rights reserved. Material data listed in this catalog supercedes all information in previous publications.



137 Kaki Bukit Avenue 1, Shun Li Industrial Park, Singapore 416003 ttselect@tts.sg Tel: 6747-8833 Fax: 6747 0370

All product dimension and material specification is as accurate as possible at time of publication.

Tan Teck Seng Electric Co. Pte. Ltd. reserves the right to change the design or specification of its products without notification. Whilst utmost care has been taken to maintain accuracy in the data, the company does not hold any responsibility for errors and accepts no liability for the use or interpretation of this data.

EMTECH® BS4568 / IEC61386 CONDUIT PIPE



Tan Teck Seng Electric Co Pte Ltd Company has been established since 1973. Being a supplier in the electrical industries for the past 3 decades, its core businesses lie in supplying electrical products to mostly M&E contractors and people in the construction and building related industries. Electrical products such as cable support system, conduits and accessories and lightning protection system are then provided.

Having been in the business of electric fittings for more than thirty years, we pride ourselves for the valuable knowledge and experience in the needs and design of conduit accessories to meet the challenge of the new millennium. In this catalogue, we offer a broad and comprehensive range of galvanized steel and brass conduit accessories which will match the demands of any projects using BS4568 / IEC61386 conduits. It is our hope that you will find the product details informative and applicable to your needs. We assure our customers that we will continue to expand and improve the range of products.

EMTEC	H BS45	568/IEC	61386 0	LASS4	OMM
EMTECH	BS4568	/IEC618	86 CLAS	S4 25MM	
EMTECH	1 BS4 56	8/IEC 61	386 CLA	S 4 32MI	M

 $CP\text{--}20\text{-}E \; / \; CP\text{--}25\text{-}E \; / \; CP\text{--}32\text{-}E$

EMTECH Brand BS4568 / IEC61386 Class 4 Hot Dipped Galvanised Steel Conduit				
Nominal	Outer D	Jiameter		Weight per
Size	Min	Max		Length
mm	mm	mm	mm	kg/length
20	19.7	20.0	1.6±0.15	±2.90
25	24.6	25.0	1.6±0.15	± 3.70
32	31.6	32.0	1.6±0.15	±4.80
Standard length 3.75m Other length available upon request.				

EMTECH BS4568/IEC 61386 CLASS 3 20MM

EMTECH BS4568/IEC 61386 CLASS 3 25MM

СР-20-Р / СР-25-Р

EMTECH Brand BS4568 / IEC61386 Class 3 Galvanised Steel Conduit				
Nominal	Outer Diameter			Weight per
Size	Min	Max	Wall Thickness ±	Length
mm	mm	mm	mm	kg/length
20	19.7	20.0	1.6±0.15	±2.70
25	24.6	25.0	1.6±0.15	±3.40
32	31.6	32.0	1.6±0.15	±4.50
Standard length 3.75m Other length available upon request.				

Epoxy Powder Coated Conduits & Accessories are available to suit your M&E services requirement.





Colour Chart (Standard Colors) The accuracy of colors shown in this chart are only as close as the printing process will allow. Other colors available upon request.

Copyright © 2008-2017 Tan Teck Seng Electric Co. Pte. Ltd. All rights reserved. Material data listed in this catalog supercedes all information in previous publications.

Tan Teck Seng Electric Co. (Pte) Ltd137 Kaki Bukit Avenue 1, Shun Li Industrial Park, Singapore 416003ttselect@tts.sgTel: 6747-8833 Fax: 6747 0370

All product dimension and material specification is as accurate as possible at time of publication.


Tan Teck Seng Electric Co. Pte. Ltd. reserves the right to change the design or specification of its products without notification.

Whilst utmost care has been taken to maintain accuracy in the data, the company does not hold any responsibility for errors and accepts no liability for the use or interpretation of this data.

BS4568 / IEC61386 EMTECH® CONDUIT BOXES



Conduit Boxes		
Finish	Hot-Dipped Galvanized	
Fixing Centre	50.8 mm ± 0.5 mm	
Size	20mm, 25mm, 32mm	



All product dimension and material specification is as accurate as possible at time of publication.

Tan Teck Seng Electric Co. Pte. Ltd. reserves the right to change the design or specification of its products without notification. Whilst utmost care has been taken to maintain accuracy in the data, the company does not hold any responsibility for errors and accepts no liability for the use or interpretation of this data.

BS4568 EMTECH® ACCESSORIES



C-E

Circular Conduit Box Cover		
Material Galvanized steel		
Finish Hot-Dipped Galvanized		
Available Sizes Small – for use with		
20mm & 25mm boxes		
Note: Rubber gasket to suit above covers		
also available on order.		

SB-20-E / SB-25-E / SB-32-E





CF-DC-20-E / CF-DC-25-E



С-В		
Circular Conduit Box Cover 32mm		
Galvanized steel		
Hot-Dipped Galvanized		
Large - for use with 32mm above sizes		
Note: Rubber gasket to suit above covers also available on order.		

S-20-Е / S-25-Е / S-32-Е

Socket	
Material	Galvanized steel
Finish	Hot-Dipped Galvanized
Available sizes	20mm ~ 32mm



Donie Cover (Screwed)	
Finish	Hot-Dipped Galvanized
Fixing Centre	50.5mm
Available sizes	20mm, 25mm

KOC1





SJ-20 / SJ-25 Socket Joint

SOCKET JOINT	
Material	Galvanized steel
Finish	Galvanized
Available sizes	20mm, 25mm

PS-25-HD / PS-32-HD

Hot Dipped Galavanized

Plain Saddle

Finish

sizes

Available

april - 2	

VO D

KOC2

K.O. Box Cover - 2 Gang		
Material	Steel	
	Plain or Hot Dipped Galvanized	

SP-20-B / SP-25-B



Stop Plugs Finish Brass Available sizes 20mm ~ 32mm Note: Larger size plugs also available upon request.

MB-20-BS-L / MB-25-BS-L / MB-32-BS-L

	Million .
1	San a Balan
1	

	Male Bush -	
Hexagon head, long type		, long type
	Finish	Brass
	Available sizes	20mm ~ 32mm



 $20mm \sim 32mm$

CF-R-20X25-E / CF-R-25X32-E		
Reducer		
Material	Brass / Alloy	
Finish	Galvanized	
Available sizes	25mm to 20mm,	
	32mm to 25mm	

LN-20 / LN-25 / LN-32 LN-20-B / LN-25-B / LN-32-B

Locknuts – Hexagon	
Material	Steel / Brass
Finish	Galvanized
Available sizes	20mm ~ 32mm

MB-20-BS / MB-25-BS / MB-32-BS

Male Bush – Hexagon head, short type	
Finish	Brass
Available sizes 20mm ~ 32mm	

Copyright © 2008-2017 Tan Teck Seng Electric Co. Pte. Ltd. All rights reserved. Material data listed in this catalog supercedes all information in previous publications.



Tan Teck Seng Electric Co. (Pte) Ltd 137 Kaki Bukit Avenue 1, Shun Li Industrial Park, Singapore 416003 ttselect@tts.sg

All product dimension and material specification is as accurate as possible at time of publication.

Tan Teck Seng Electric Co. Pte. Ltd. reserves the right to change the design or specification of its products without notification.

Whilst utmost care has been taken to maintain accuracy in the data, the company does not hold any responsibility for errors and accepts no liability for the use or interpretation of this data.

C-B

KNOCK-OUT (KO) BOXES









KO1E

Steel Switch & Socket Box - 1 Gang (BS4662)		
Material Galvanized Steel Sheet		
Finish	Galvanized	
Dimension	75 x 75 x 35mm	
Fixing Centre	60.3mm to suit standard BS switch & socket outlets (Tapped earth hole at base of box)	

KO2E

Steel Switch & Socket Box - 2 Gang (BS4662)		
Material	Galvanized Steel Sheet	
Finish	Galvanized	
Dimension	135 x 75 x 35mm	
Fixing Centre	120.6mm to suit standard BS switch & socket outlets (Tapped earth hole at base of box)	

KO1-CD-HD

1G Hot Dipped CD Shelter Box	
Material	Steel Sheet
Finish	Hot Dipped Galvanized
Dimension	75 x 75 x 35mm
Fixing Centre	60.3mm to suit standard BS switch & socket outlets (Tapped earth hole at base of box)

KO2-CD-HD

2G Hot Dipped CD Shelter Box	
Material	Steel Sheet
Finish	Hot Dipped Galvanized
Dimension	135 x 75 x 35mm
Fixing Centre	120.6mm to suit standard BS switch & socket outlets (Tapped earth hole at base of box)

Copyright $\ensuremath{\mathbb{C}}$ 2008-2017 Tan Teck Seng Electric Co. Pte. Ltd. All rights reserved. Material data listed in this catalog supercedes all information in previous publications.



137 Kaki Bukit Avenue 1, Shun Li Industrial Park, Singapore 416003

All product dimension and material specification is as accurate as possible at time of publication.

Tan Teck Seng Electric Co. (Pte) Ltd

Tan Teck Seng Electric Co. Pte. Ltd. reserves the right to change the design or specification of its products without notification. Whilst utmost care has been taken to maintain accuracy in the data, the company does not hold any responsibility for errors and accepts no liability for the use or interpretation of this data.

EMTECH® FLEXIBLE CONDUIT




PVC Coated Galvanized Flexible conduit fitted with a flexible adapter

PCF

PVC-Coated Galvanized Flexible Conduit		
Features	Water resistant, with maximum protection against most liquids and solid particles. High temperature heat resistance and self extinguishing black pvc sheathing. Manufactured to withstand vibrations of installations and equipment. Flexibility in installation. Wide range of conduit sizes.	
Applications	Wide range of conduit sizes. Provide maximum protection of cables in installation against ingress of solid particles and liquids. It can be installed in most electrical applications where a good protective support for cables are needed. Used in areas as diverse as building automation systems, underfloor, machinery, air-con controls, lightning and power circuits installations and many other applications where good electrical support systems are needed.	

Catalogue Number	Outgoing G.I. Conduit Size (inch)	Length per coil (feet)
PCF16	5/8"	100
PCF20	3/4"	100
PCF25	1"	100
PCF32	11/4"	50
PCF38	11/2"	50
PCF50	2"	50
PCF63	21/2"	30
PCF75	3"	30
PCF100	4"	30

CF-BA





MI Flexible Adaptors Material Malleable Iron	
sizes32mm, 38mm, 50mmNote: Larger sizes also available upon request.	

Flexible Steel Conduit		
Material	Galvanized steel	
Finish	Plain galvanized - unmarked	
Available sizes	³ / ₄ ", 1", 1 ¹ / ₄ ", 1 ¹ / ₂ ", 2"	
Steel flexible conduit offers good mechanical protection when compared against upvc type.		
1	1 8 1 71	

EM			
Nickel Plated Flexible Adaptors			
Finish	Nickel Plated		
Available	³ / ₄ " x ⁵ / ₈ ", ³ / ₄ " x ³ / ₄ ", 1" x		
sizes	³ / ₄ ", 1" x 1", 1 ¹ / ₄ " x 1		
	¹ / ₄ ", 1 ¹ / ₂ " x 1 ¹ / ₂ ", 2" x 2",		
	20 x 5/8, 20 x ³ / ₄ , 25 x ³ / ₄ ,		
	25 x 1		



EMTECH - Low Smo	ke Covered Flexible Conduit	
Usage	EMTECH – Low Smoke covered steel flexible conduit is ideal for use	P
	in areas where fire is of particular concern.	r
		P
Properties	Resistance to flame, low (toxicity, smoke density)	Р
PSB Test Standard	IEC 61034 Part 2	Р

Item Number	Nominal Size	Length of Each Roll ft
PCF16-LSOH	16mm	100
PCF20-LSOH	20mm	100
PCF25-LSOH	25mm	100
PCF32-LSOH	32mm	50
PCF38-LSOH	38mm	50
PCF50-LSOH	50mm	50

Nickel Plated Flexible Adapter



Copyright © 2008-2017 Tan Teck Seng Electric Co. Pte. Ltd. All rights reserved. Material data listed in this catalog supercedes all information in previous publications.

Tan Teck Seng Electric Co. (Pte) Ltd

137 Kaki Bukit Avenue 1, Shun Li Industrial Park, Singapore 416003 ttselect@tts.sg

All product dimension and material specification is as accurate as possible at time of publication.

Tan Teck Seng Electric Co. Pte. Ltd. reserves the right to change the design or specification of its products without notification.

Whilst utmost care has been taken to maintain accuracy in the data, the company does not hold any responsibility for errors and accepts no liability for the use or interpretation of this data.

OTHER TOOLS & ACCESSORIES



137 Kaki Bukit Avenue 1, Shun Li Industrial Park, Singapore 416003 ttselect@tts.sg

All product dimension and material specification is as accurate as possible at time of publication.

Tan Teck Seng Electric Co. Pte. Ltd. reserves the right to change the design or specification of its products without notification.

Whilst utmost care has been taken to maintain accuracy in the data, the company does not hold any responsibility for errors and accepts no liability for the use or interpretation of this data.

EMTECH® PROJECT REFERENCE

BS4568 CLASS 4 PROJECT REFERENCE PROJECT CONSULTANT

CONSULIANT	
Parsons Brinckerhoff Pte Ltd	
CPG Consultants Pte Ltd	
Jacobs Lend Lease	
Defence Science and Technology Agency	
CPG Consultants Pte Ltd	
EM Services Pte Ltd	
LTA	
Jacobs Engineering	
Squire Mech	
Meinhardt (S) Pte Ltd	
Squire Mech	
Parsons Brinckerhoff Pte Ltd	

BS4568 CLASS 3 PROJECT REFERENCE

PROJECT	CONSULTANT	
Hoy Fatt Rd 6th Storey Factory	PTP Engineers	
KLA Serangoon North Factory	ory HY M&E	
Marina Barrage	CDM SG Pte Ltd	
IM Flash	M+W Zander (S) Pte Ltd	
Avenue Park Condo	Rankine & Hill (S) Pte Ltd	
60 Robinson Rd	JRP	
Siltronic	M+W Zander (S) Pte Ltd	
Buckley 18	Mott MacDonald Singapore Pte Ltd	
The Rochester	J Roger Preston (S) Pte Ltd	
Orchard Residences	Squire Mech Pte Ltd	
ITE West	APP Engineering Pte Ltd	

Copyright © 2008-2017 Tan Teck Seng Electric Co. Pte. Ltd. All rights reserved.

All content in this catalogue, including (but not limited to) the layout, design, images, brand names and other information, are protected by copyright and other intellectual property laws. Except when expressly permitted under these laws, no part of the information contained herein may be reproduced or transmitted in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise), or used for advertising or promotional purposes, general distribution, creating new collective works, or for resale, without prior written permission of Tan Teck Seng Electric Co. Pte. Ltd.

All product dimension and material specification is as accurate as possible at time of publication. Tan Teck Seng Electric Co. Pte. Ltd. reserves the right to change the design or specification of its products without notification. Whilst utmost care has been taken to maintain accuracy in the data, the company does not hold any responsibility for errors and accepts no liability for the use or interpretation of this data.

Tan Teck Seng Electric Co. (Pte) Ltd

137 Kaki Bukit Avenue 1, Shun Li Industrial Park, Singapore 416003 ttselect@tts.sg